

INTELLOFAX 18

REPORT NO.

CD NO.

NO. OF PAGE'S 1

NO. OF ENCLS.
(LISTED BELOW)

SUPPLEMENT TO
REPORT NO.

25X1

THIS DOCUMENT CONTAINS INFORMATION AFFECTING THE NATIONAL DEFENSE OF THE UNITED STATES, WITHIN THE MEANING OF TITLE 18, SECTIONS 793 AND 794, OF THE U. S. CODE, AS AMENDED. ITS TRANSMISSION OR REVELATION OF ITS CONTENTS TO OR RECEIPT BY AN UNAUTHORIZED PERSON IS PROHIBITED BY LAW. THE REPRODUCTION OF THIS FORM IS PROHIBITED.

25X1

THIS IS UNEVALUATED INFORMATION
REFERENCE COPY
DO NOT CIRCULATE

Aviation gasoline is produced in the Leuna (M 52/D 91), Boehlen (M 52/K 29) and Zeitz (M 52/K 08) plants. Standard gasoline is not used as an intermediate product. Instead, the aviation gasoline is produced directly from the crude oil by hydrogenation. Large amounts of isooctane are also produced in the Soviet Zone. Production figures were not available. The entire aviation gasoline production is shipped to the U.S.S.R. where about 1 kg. of fluid is added to each 1,000 liters of gasoline. Source did not know the octane number of the gasoline. *

25X1

Comment. To date, only the Boehlen hydrogenation plant has been definitely known to produce aviation gasoline. The fluid added to the gasoline is ethyl fluid which consists of tetraethyl lead ($Pb(C_2H_5)_4$), ethylene dibromide (CH_2Br-CH_2Br) and ethylene dichloride (CH_2Cl-CH_2Cl). As no information is available concerning the quality of the aviation gasoline, it cannot be determined which octane number is achieved at a ratio of 1,000 liters of aviation gasoline to 1 kg of ethyl fluid.

CLASSIFICATION **SECRET**

STATE	#	NAVY	NSRB	DISTRIBUTION			
ARMY	#	AIR	FBI	OSI	BI		